

Plymouth

plymouthrubber.com








**VINYL &
RUBBER
ELECTRICAL TAPES**
MANUFACTURERS SINCE 1896



**SOLUTIONS FOR
ELECTRICAL
PROFESSIONALS**




PROFESSIONAL GRADE - HIGH PERFORMANCE

Tape	Product Description	Standard Sizes	Plymouth Code	Compare with	Packaging
High Adhesion Heavy duty Grade SLIPKNOT GOLD 8.5	 <p>A 8.5 mil premium vinyl electrical tape included in our new Slipknot Vinyl series. Specially designed to achieve higher adhesion and conformability. This 20% thicker heavy duty tape allows higher resistance and faster build up. Primary insulation for splices up to 600V, protective outer jacket over splices and for all medium cold and hot weather applications.</p> <p>-10°C to 105°C / 14°F to 221°F</p>	3/4" x 66'	4550	Super 88	100/case PC Multiple 5r pack
		3/4" x 66'	4551	Super 88	100/case Carboard box - Multiple 5r Eco-Pack
High Adhesion Professional Grade SLIPKNOT GOLD 7.0	 <p>A 7.0 mil premium vinyl electrical tape included in our new Slipknot Vinyl series. Specially designed for professional use to achieve higher adhesion and conformability. Primary insulation for splices up to 600V, protective outer jacket over splices and for all medium cold and hot weather applications.</p> <p>-10°C to 105°C / 14°F to 221°F</p>	3/4" x 66'	4570	Super 33+	100/case PC Multiple 5r pack
		3/4" x 66'	4571	Super 33+	100/case Carboard box - Multiple 5r Eco-Pack
Excellent Elasticity Heavy duty Grade SLIPKNOT PLATINUM 8.5	 <p>A 8.5 mil premium vinyl electrical tape included in our new Slipknot Vinyl series. Excellent elasticity and performance even in the coldest weather. This 20% thicker heavy duty tape allows higher resistance and faster build up. Primary insulation for splices up to 600V, protective outer jacket over splices and for all low temperature applications.</p> <p>-18°C to 105°C / 0°F to 221°F</p>	3/4" x 66'	4240	Super 88	100/case PC Multiple 5r pack
		3/4" x 66'	4275	Super 88	100/case Carboard box - Multiple 5r Eco-Pack
Excellent Elasticity Heavy duty Grade SLIPKNOT PLATINUM 7.0	 <p>A 7.0 mil premium vinyl electrical tape included in our new Slipknot Vinyl series. Specially designed for professional use with excellent elasticity even in cold weather applications. Primary insulation for splices up to 600V, protective outer jacket over splices and for all low temperature applications.</p> <p>-18°C to 105°C / 0°F to 221°F</p>	3/4" x 66'	4453	Super 33+	100/case PC Multiple 5r pack
		3/4" x 66'	4454	Super 33+	100/case Carboard box - Multiple 5r Eco-Pack
Heavy Duty Grade Special Size SLIPKNOT P85	 <p>A 8.5 mil premium vinyl electrical tape included our new Slipknot vinyl series. A selection of higher widths of our excellent elasticity tape for special uses. This 20% thicker heavy duty tape allows higher resistance and faster build up. Primary insulation for splices up to 600V, protective outer jacket over splices and for all low temperature applications.</p> <p>-18°C to 105°C / 0°F to 221°F</p>	1" x 108'	4268	Super 88	80/case C
		1 1/2" x 108'	4273	Super 88	50/case C
		2" x 108'	4274	Super 88	40/case C

NEW PREMIUM SLIPKNOT


VINYL ELECTRICAL TAPES

PROFESSIONAL GRADE – HIGH PERFORMANCE

Tape	Product Description	Standard Sizes	Plymouth Code	Compare with	Packaging
Excellent Elasticity Special Size SLIPKNOT P111	 A 7.0 mil premium vinyl electrical tape included our new Slipknot vinyl series. A selection of higher widths of our excellent elasticity tape for professional special uses. Primary insulation for splices up to 600V, protective outer jacket over splices and for all low temperature applications. -18°C to 105°C / 0°F to 221°F	1" x 66'	4457	Super 33+	80/case C
		1 1/2" x 66'	4458	Super 33+	100/case C
		2" x 66'	4461	Super 33+	40/case C
Color Coding Vinyl Electrical Tape PREMIUM 37	 A 7 mil professional grade available in nine colors for color coding with an excellent elasticity and insulating properties. High resistance against abrasion, water, oil, alkalis, acids and corrosive chemicals. Use for quick identification of electrical circuits, containers and conduit systems as well as primary insulation for splices at not more than 600V. 0°C to 105°C / 32°F to 221°F	3/4" x 66'	3702	35	20/case PC
		3/4" x 66'	3703	35	20/case PC
		3/4" x 66'	3704	35	20/case PC
		3/4" x 66'	3705	35	20/case PC
		3/4" x 66'	3706	35	20/case PC
		3/4" x 66'	3707	35	20/case PC
		3/4" x 66'	3708	35	20/case PC
		3/4" x 66'	3709	35	20/case PC
		3/4" x 66'	3711	35	20/case PC
Extra Heavy Duty Vinyl Electrical Tape HD2	 A 10 mil heavy duty, general purpose tape. Additional thickness allows for quicker build-ups and added abrasion protection in all types of mechanical and electrical applications. Primary insulation for splices at not more than 600V. -18°C to 105°C / 0°F to 221°F	2" x 108'	8724	22	40/case C

NEW PREMIUM SLIPKNOT







GENERAL PURPOSE GRADE

Tape	Product Description	Standard Sizes	Plymouth Code	Compare with	Packaging
General Purpose Vinyl Electrical Tape REVERE	 A 7 mil general purpose grade characterized by its excellent performance and high durability, with good elasticity, level of adhesion and insulating properties. Resists abrasion, water, oil, alkalis, acids and corrosive chemicals. Available in nine colors for color coding, harnessing, protective jacketing as well as primary insulation for splices at not more than 600V. -10°C to 105°C / 14°F to 221°F	3/4" x 60'	3119	Temflex 1700	100/case C T5
		3/4" x 60'	3898	Temflex 1700 C	50/case C T5
		3/4" x 60'	3899	Temflex 1700 C	50/case C T5
		3/4" x 60'	3900	Temflex 1700 C	50/case C T5
		3/4" x 60'	3901	Temflex 1700 C	50/case C T5
		3/4" x 60'	3902	Temflex 1700 C	50/case C T5
		3/4" x 60'	3903	Temflex 1700 C	50/case C T5
		3/4" x 60'	3904	Temflex 1700 C	50/case C T5
		3/4" x 60'	3905	Temflex 1700 C	50/case C T5







LOOKING FOR SOMETHING ELSE?

We are MANUFACTURERS

This list is reflective of stocked items, other sizes and packaging are available. Contact our customer service office or your representative agent to attend to your needs.

Tape	Product Description	Standard Sizes	Plymouth Code	Compare with	Packaging
Linerless High Voltage Rubber Tape L969 PLYVOLT	 <p>A 30 mil self-bonding, thermally conductive tape, for insulating and jacketing splices through 69kV.</p> <p>Continuous 90°C / 194°F Overload 130°C / 266°F</p>	3/4" x 30'	2211	130C	60/case B
		1" X 30'	2212	130C	40/case B
		1 1/2" X 30'	2213	130C	30/case B
		2" X 30'	2214	130C	40/case C
High and Low Voltage Rubber Insulating Tape with Liner W963 PLYSAFE	 <p>A 30 mil High and Low voltage self-amalgamating tape for insulating and jacketing splices through 69kV.</p> <p>Continuous 90°C / 194°F Overload 130°C / 266°F</p>	3/4" x 30'	2117	23	60/case B
		1" X 30'	2132	23	40/case B
		1 1/2" X 30'	2134	23	30/case B
		2" X 30'	2145	23	40/case C
High Voltage Insulating Tape 3 BI-SEAL	 <p>Available in 20 mil and 30 mil. A polyethylene and EPR High voltage self-amalgamating tape possessing superior electrical, mechanical and thermal properties. For insulating and jacketing splices through 69kV and for building stress cones and jacketing of terminations on power cable from 600V through 35kV.</p> <p>Continuous 90°C / 194°F Overload 130°C / 266°F</p>	3/4" x .020" x 30'	8051		100/case C
		1" x .030" x 30'	8066		80/case C
Low Voltage Rubber Splicing Tape 122 RUBBER	 <p>A 30 mil economical self-amalgamating tape which can be used as a primary insulation for splices at not more than 600V when used in conjunction with a friction or vinyl jacketing tape.</p> <p>80°C / 176°F</p>	3/4" x 22'	2002	2155	100/case C
		2" x 22'	2020	2155	40/case C
Low Voltage Rubber Splicing Tape 150 ASTM	 <p>A 30 mil self-amalgamating tape which can be used for insulating cables splices through 2kV, in conjunction with a jacketing tape.</p> <p>Continuous 80°C / 176°F Overload 95°C / 203°F</p>	3/4" x 30'	2006		100/case C
EPR Semi-Conducting Tape 17 PLYSHIELD	 <p>A 30 mil self-amalgamating, conducting tape for shielding High Voltage splices and terminations.</p> <p>Continuous 90°C / 194°F Overload 130°C / 266°F</p>	3/4" x 15'	2104	13	50/case B

INSULATING & SPLICING TAPES

Tape	Product Description	Standard Sizes	Plymouth Code	Compare with	Packaging
Electrical Filler Tape 125 FILLER	 <p>A 125 mil self-amalgamating, low voltage insulating compound designed for quick, void-free insulation build-up. It can be easily molded by hand to conform to irregular shapes and can be used as primary insulation for splices through 5kV in conjunction with other insulating tapes.</p> <p>Continuous 80°C/176°F Overload 95°C/203°F</p>	1 1/2" x 5'	2074	Scotchfill	30/case B
Tinned Copper Shielding Tape 15 PLYBRAID	 <p>A tinned copper mesh-knit shielding with exceptional conformability and temperature stable for replacing metallic shield in shielded cable repair.</p>	2" x 10' 1" x 15' 1" x 100'	2230 5415 5416	24 24 24	40/case 50/case B 16/case B
Tinned Copper Ground Braid PLYSTRAP	 <p>A woven tinned copper braid, high current capacity of #9 AWG solid cooper; used for grounding high voltage splices and terminations</p>	3/8" x 100'	2711	25	1/case
Silicone Rubber Tape 20 PLYSIL	 <p>A 20 mil triangular cross-section, self fusing tape, arc and track resistance, used for jacketing high voltage terminations on solid dielectric cable through 69kV.</p> <p>180°C / 356°F</p>	1" x 30'	3455	70	50/case B
Arc and Fireproofing Tape 53 PLYARC	 <p>A 30 mil Elastomeric tape that provides excellent flame and arc protection for all types of cables. Easily visible, easy inspection. When exposed to flame will generate a thermally insulating residue for cable protection.</p>	1 1/2" x 20' 3" x 20'	3817 3819	77 77	40/case C 20/case C
Varnished Dacron Glass Tape 61 and 61A	 <p>A fine weave of Dacron and fiber glass threads, impregnated with a fully cured polyester coating which provides excellent electrical and mechanical protection. Available without (61/7mil) and with adhesive (61A/8 mil).</p> <p>Continuous 155°C / 311°F Overload 185°C / 365°F</p>	3/4" x 60' 3/4" x 60'	1101 (without adhesive) 1121 (with adhesive)	2510 2520	40/case C 40/case IB

LOOKING FOR
SOMETHING ELSE?

We are MANUFACTURERS

This list is reflective of stocked items, other sizes and packaging are available. Contact our customer service office or your representative agent to attend to your needs.

Tape		Product Description	Standard Sizes	Plymouth Code	Compare with	Packaging
Vinyl Mastic VM		A self-fusing mastic compound with an all weather vinyl backing that adds UV protection. It can be used for insulating and watersealing electrical connections through 600V . Excellent electrical properties, superior adhesion, moisture and chemical resistance. Continuous 90°C/194°F Overload 130°C/266°F	4" x 10'	2609	2200	10/case IB
Rubber Mastic RM		A self-bonding rubber tape bonded to a tacky electrical grade mastic. Use for insulating and moisture sealing splices and terminations on solid dielectric cables. Excellent electrical properties, superior adhesion, moisture and chemical resistance as well as surface protection. Continuous 90°C/194°F Overload 130°C/266°F	1 1/2" x 10' 2" x 10'	2619 2625	2228 2228	30/case IB 30/case B
Insulating Mastic 10 PLYSEAL		A self-amalgamating insulating mastic for insulating and sealing all types of overhead and direct buried electrical connections up to 600V . Excellent adhesion to metals, cable insulations and jackets. For watersealing duct work cable ends and all types of splices. Continuous 90°C/194°F Overload 130°C/266°F	3 3/4" x 10' 3 3/4" x 3 3/4"	2626 2627	2229 2229	10/case B 300/case
Electrical Filler Insulating Mastic PLYFILL		Plyfill is a self-amalgamating low voltage insulating mastic, designed for quick void-free insulation build-up. Easily molded by hand. Continuous 90°C/194°F Overload 130°C/266°F	1 1/2" x 5'	2644	Scotchfill	12/case B
Sealing and Water-proofing Mastic WATERSEAL		A self-amalgamating mechanical grade mastic used for sealing and water-proofing. Excellent adhesion to metals, cable insulations and jackets. Ideal for molding and conforming to irregular shapes. -10°C to 90°C 14°F to 194°F	1 1/2" x 4'	2848		40/case C
Vinyl Reinforced Insulating Mastic 4000 PLYSEAL-V		Permanently seal and insulate sub-surface and overhead low voltage electrical connections. Preferred for cold weather applications. Continuous 90°C/194°F Overload 130°C/266°F	4" x 10' 4" x 6 1/2"	2620 2622	2200 2210	10/case B 100/case
High Voltage Rubber backed Insulating Mastic 5000 BUS-SEAL		A laminate of W963 Plysafe and 10 Plyseal insulating mastic. A one-pass application of this laminate provides high dielectric strength, instant, adhesion and excellent conformability. For insulating and water-proofing high voltage bus connectors and conductors. Corrosion protection for junction boxes, bus-duct and cable tray joints. Continuous 90°C/194°F Overload 130°C/266°F	4" x 10'	8371		10/case B

LOOKING FOR
SOMETHING ELSE?

We are MANUFACTURERS







This list is reflective of stocked items, other sizes and packaging are available. Contact our customer service office or your representative agent to attend to your needs.

Tape	Product Description	Standard Sizes	Plymouth Code	Compare with	Packaging	
Corrosion protection Vinyl Tape PLYWRAP 11		A corrosion protection pressure sensitive vinyl tape giving complete environmental, mechanical and electrical protection for all types of pipewrapping applications. UV, bacteria and fungus resistance. It can be used for both overhead and direct burial applications. -18°C to 105°C / 0°F to 221°F	1" x 100'	4610	50	48/case C
			2" x 100'	4611	50	24/case C
Jacketing Tape 44 NEOPRENE		A 30 mil self-amalgamating neprene tape specially formulated for permanent protection of cables exposed to oil, grease and other hydrocarbons. Chemical, weather and flame resistance.	2" x 30'	8264		40/case C
Telecom Double Rubber Tape DR		Non-adhesive, self-bonding communications tape used for critical sealing and re-jacketing. Maintains gas pressure in pressurized cable. Communications Industry DR Specifications TL-192 and 6863.	3/4" x 15'	2011		100/case C
			2" x 15'	2013		40/case C
Telecom Cohesive Rubber Tape CR		The industry standard for temporary splice coverings on communication and control cables. Consist of one soft, uncured layer bonded to a cured, abrasio-resistant layer. Unique separator allows controlled removal at the user's discretion. An air-tight, water-proof, gas-tight seal is formed when the uncured layer is bonded to itself. maintains gas pressure in pressurized cable. Communications Industry Specification 7144.	28" x 20'	2065		1/case IB
			36" x 20'	2110		1/case IB
Glass Cloth Tape 77 PLYGLAS		A 7 mil woven glass fabric tape with a thermosetting rubber based adhesive used for protecting and insulating high temperature connections (130°C/266°F), such as motor leads and transformed windings. High tensile strength for splice reinforcement. Excellent tear and abrasion resistance. Up to 130°C / Up to 266°F	1/2" x 66'	3451	27	50/case B
			3/4" x 66'	3456	27	50/case B
			1" x 108'	3459	27	20/case C
Glass Cloth Tape 77 PLYGLAS HT NEW		A 7 mil woven glass fabric tape with a heat resistant silicone adhesive for high temperature applications. Used in applications where solvent resistance, flame retardant and abrasion resistance is required. Up to 200°C/ Up to 392 °F - Class N	3/4" x 66'	3461	69	50/case B
Heavy Duty Cloth Duct Tape PLYDUCT 48		A premium duct tape that provides excellent adhesion to all types of surfaces. Laminated cloth construction provides superior mechanical strength and will conform to irregular surfaces. Up to 65°C / Up to 149°F	2" x 60 yds	3150	3939	24/case C
Rubberized textile tape / Friction Tape 100 ASTM & 170 BROWN		A high quality cotton fabric coated on both sides with a black rubber adhesive compound which provides good adhesion to all types of surfaces and excellent adhesion against abrasion.	3/4" x 60'	1002	1755	100/case C
			3/4" x 82'	1012	1755	100/case C
			2" x 36'	1015	1755	60/case C
			1 1/2" x 60'	1038	1755	50/case C
			2" x 60'	1039	1755	40/case C
			1 1/2" x 82'	1047	1755	50/case C
			3/4" x 70'	1008		100/case C
			2" x 70'	1057		40/case C

MINING TAPES

Plymouth

plymouthrubber.com

Tape	Product Description	Standard Sizes	Plymouth Code	Compare with	Packaging
Mining Grade Vinyl Electrical Tape PLYTUFF	 <p>A 7 mil jacketing tape specifically formulated for flame resistance and abrasion resistance. Use for repairing nicks and tears in all mining cables. Printed for use in MSHA approved splicing kits. Use this tape for primary insulation through 600V. -10°C to 80°C / 14°F to 176°F</p>	3/4" x 66'	3880	Temflex 1700 P	100/case C
		1 1/2" x 66'	3881	Temflex 1700 P	100/case C
Linerless High Voltage Rubber Tape L969 PLYVOLT	 <p>A 30 mil self-bonding, thermally conductive tape, for insulating and jacketing splices through 69kV. Continuous 90°C / 194°F Overload 130°C / 266°F</p>	3/4" x 30'	2211	130C	60/case B
		1" X 30'	2212	130C	40/case B
		1 1/2" X 30'	2213	130C	30/case B
		2" X 30'	2214	130C	40/case C
Rubber Mastic RM	 <p>A self-bonding rubber tape bonded to a tacky electrical grade mastic. Use for insulating and moisture sealing splices and terminations on solid dielectric cables. Excellent electrical properties, superior adhesion, moisture and chemical resistance as well as surface protection. Continuous 90°C / 194°F Overload 130°C / 266°F</p>	1 1/2" x 10'	2619	2228	30/case IB
		2" x 10'	2625	2228	30/case B
High Voltage Insulating Tape 3 BI-SEAL	 <p>Available in 20 mil and 30 mil. A polyethylene and EPR High voltage self-amalgamating tape possessing superior electrical, mechanical and thermal properties. For insulating and jacketing splices through 69kV and for building stress cones and jacketing of terminations on power cable from 600V through 35kV. Continuous 90°C / 194°F Overload 130°C / 266°F</p>	1" x .030" x 30'	8066		80/case C
Mining Grade Cable Jacket Repair Wrap GLF	 <p>A unique laminate of special formulated Hypalon backing and a flame retardant Mastic possessing an extremely abrasion resistance as well as an excellent moisture exclusion properties. Designed for repairing and splicing trailing cables and conduit. The laminate is easy to apply and remains flexible at low temperatures. MSHA approval printed.</p>	2" x 6'	2563	Scotch 31	30/case C
		2" x 8.5'	2564	Scotch 31	20/case C
Mining Grade Cable Jacket Repair Wrap GLF2	 <p>A special GLF laminate with an additional guideline tacky flame retardant mastic layers possessing a superior abrasion and moisture resistance. Designed for repairing and splicing trailing cables and conduit. The laminate is very easy to apply and remains flexible at low temperatures. MSHA approval printed.</p>	2" x 7'	2501		30/case C
		2" x 9.5'	2502		30/case C
Hypalon Vulcanizable Jacketing compound	 <p>A vulcanizable hypalon compound that flows easily within the range of mold temperatures from 260°F-330°F (127°C-166°C). Bonds readily to neoprene, hypalon, PVC and NBR-PVC jackets without the need of a bonding agent. P-153-MSHA Acceptance.</p>	1 1/2" x 30'	2048		40/case C
		1 1/2" x 30'	2049		40/case C

Packaging Legend:

PC = Plastic Can IB = Individual Bag
C = Cello Wrapped B = Box
T5 = Tower 5 rolls

LOOKING FOR SOMETHING ELSE?

We are MANUFACTURERS

This list is reflective of stocked items, other sizes and packaging are available. Contact our customer service office or your representative agent to attend to your needs.

	PLYMOUTH Product	Representative Cat. No.	Compare With	
VINYL ELECTRICAL TAPES	Premium Slipknot Gold 7.0	4570, 4571	Super 33+	
	Professional Grade 7 mils	Premium Slipknot Platinum 7.0	4453, 4454	Super 33+
		Premium 37 (color coding)	3702 - 3711	35
	Professional Grade 8.5 mils	Premium Slipknot Gold 8.5	4550, 4551	Super 88
		Premium Slipknot Platinum 8.5	4240, 4275	Super 88
	Heavy Duty Grade 10 mils	HD2	8723 - 8724	22
	General Purpose Grade	Revere Black	3119	Temflex 1700
		Revere Colors (color coding)	3898 - 3905	Temflex 1700 C
	Other Uses	Plywrap 11 Vinyl Pipewrap	4611	50
		Plycom G-Vinyl	4318	88T
	Plytuff Printed Mining	3880	Temflex 1700 P	
FRICITION AND LOW VOLTAGE RUBBER TAPES	100 ASTM Friction	1002	1755	
	170 Brown Friction	1008	-	
	122 Rubber Tape	2002	2155	
	150 ASTM Rubber	2006	-	
	Plyfill / 125 Filler	2644 / 2074	Scotchfill	
INSULATING MASTICS	10 Plyseal (Rolls & Pads)	2626-2628	2229	
	4000 Plyseal-V (Rolls & Pads)	2620-2622	2200-2210	
	5000 Bus Seal	8371	-	
	RM Tape	2625,2619,2719	2228	
	VM Tape	2617,2618,2609	2210	
	Waterseal Mastic	2856	-	
HIGH VOLTAGE INSULATING & SHIELDING TAPES	L969 Plyvolt Linerless	2211	130C	
	W963 Plysafe	2117	23	
	W962 EPR	8080	-	
	3 Bi-Seal	8051-8054	-	
		8065-8068	-	
	17 Plyshield	2104	13	
	15 Plybraid	5415	24	
	Plystrap	2711	25	
SPECIAL PURPOSE PRODUCTS	Plyduct 48	3150	3939	
	20 Pylsil	3455	70	
	53 Plyarc	3819	77	
	77 Plyglas	3456	27	
	77 Plyglas HT	3461	69	
	44 Neoprene	8261	-	
	61-A Varnished Dacron-Glass	1121	2520	
	61 Varnished Dacron-Glass	1101	2510	
	Plyprep Cable Prep Kit	2684	CC-2	
HIGH VOLTAGE TERMINATION & SPLICE KITS	ColdTerm Outdoor/Indoor	2801,2802,2803	Quick Term Series	
JACKET REPAIR	GLF	2563, 2564	Scotch 31	
	GLF2	2501, 2502	-	

PLYMOUTH RUBBER GROUP



CERTIFICATIONS OF OUR QUALITY ASSURANCE SYSTEMS

PLYMOUTH RUBBER GROUP was born from the merger of the three major brands in the market for Power Tapes: Plymouth Rubber Company (USA), Bishop (USA) and AINSA (Spain).

Throughout our whole history, we have been doing our best efforts to keep the know-how and expertise of these three companies, which combined, add up to more than 100 years of work in the electrical tape industry.

Ever since the Group was created we have been using this rich background to stay strong in innovation within different sectors, focusing on our objective which is paying attention to the electrical professional needs and remaining at their service.



LIMITED WARRANTY:

Plymouth warrants that each of its products will substantially conform to that product's written specifications exclusively contained in its Plymouth product data sheet for a period of one (1) year from the date of shipment, (unless provided otherwise in product's data sheet). Plymouth makes or gives no warranty to the distributor, its customers, or the product's end user regarding the product's merchantability and/or suitability for its intended use or purpose, and buyer shall assume all risks associated therewith. Provided that the product is proved to be defective within the terms described above, and provided buyer shall have first complied with all return policies of Plymouth, Plymouth's sole obligation and Buyer's exclusive remedy under this Product Warranty shall be through the Distributor; to replace such quantity of the Product as is proved to be defective within the time period specified above. Except as expressly set forth herein, Plymouth makes or gives no other Warranties, express or implied. In no event shall Plymouth be liable for collateral, consequential, indirect or incidental damages arising out of, or connected in any way with, the supply of products.

RETURN GOODS POLICY:

1. Return of goods for any reason must be authorized by the customer service department, Plymouth Rubber Europa, Canton, MA 02021.

NO RETURN WILL BE ACCEPTED unless accompanied by a Return Goods Authorization (RGA) form, obtained from customer service. All materials approved for return must be in the original packaging, in full case amounts, purchased within the last 12 months (3 months for 44 Neoprene) and a PO # will be requested for the items you wish to return to validate the date of purchase and the material must be resalable to other customers.*

2. No partial cases, no expired material or material close to their expiration date will ever be approved for a return. All approved returns will be inspected at the warehouse to make sure all these requirements are met before any credit will be issued. If materials returned fail these criteria, no credit will be issued to the customer.

***All approved returns will be at the customer's expense for freight and will also incur a 15% restocking fee before a credit is issued to the customer**

3. All Warranty returns must be made in accordance with the terms of Plymouth's written Limited Warranty. Such returned products must be returned in their original package and in saleable condition. All freight charges for legitimate Warranty returns will be paid by Plymouth. If the return is due to an order processing error on our part, full credit will be issued for all material plus freight if notified within 30 days of receipt of the goods.

PLYMOUTH RUBBER EUROPA, S.A.U. WORKS WITH REGISTERED TRADEMARKS, AND HAS THE EXCLUSIVE RIGHT TO USE THEM.



OFFICE HOURS
8AM to 4:45PM

USA COMMERCIAL OFFICE:
960 TURNPIKE STREET, SUITE 2A
CANTON, MASSACHUSETTS
1 - 800 - 458 - 0336
INFO-USA@PLYMOUTH RUBBER.COM

HEAD OFFICE AND FACTORIES:
CTRA. SALCEDA, KM. 1,5
36400 PORRIÑO SPAIN
(+34) 986 330 562
INFO@PLYMOUTH RUBBER.COM

Plymouth
plymouthrubber.com